



Product data

Specification item	Value	Unit
Product name	PROFESSIONALE IN DALI 40	
Order code	127481	
EAN (GTIN)	8010703859708	
Pieces per box	30	
Product weight	180	Gr
Made in	Italy	

Electrical input data

Specification item	Value	Unit	Condition
Rated input voltage	220...240	Vac	
Input voltage AC range	198...264	Vac	
Input voltage DC range	176...275	Vdc	Factory default 100% EOFi= 1
Rated input frequency	50...60	Hz	
Rated input current	0,194	A	Referred to Vin = 230 V, 100% load
Rated input power	44,60	W	Referred to Vin = 230V, 100% load
Power factor	0,95	λ	
THD	< 10	%	Referred to Vin = 230 V, 100% load
Efficiency	90	%	Referred to Vin = 230 V, 100% load
Stand-by Power	< 0,5	W	
Isolation input to output	SELV		

Electrical output data

Specification item	Value	Unit	Condition
Regulation method	Constant current		
Output voltage	10...54	Vdc	
Output voltage max.	59	V	Open load
Output current	300...1050	mA	
Output current min programmable	300	mA	
Output current min dimming	7	mA	
Output current tolerance	5	%	
Output power	3...40	W	
Output current ripple	< 3	%	
Output Pst LM	< 1		
Output SVM	< 0,4		

Operating window 230V

Pout W	Vout DC	Iout mA
6,8	10...54	300
8	10...54	350
9,4	10...54	400
10,8	10...54	450
12,15	10...54	500
13,5	10...54	550
14,8	10...54	600
16	10...54	650
17,5	10...54	700
19	10...54	750
20	10...50	800
20	10...47	850
20	10...45	900
20	10...42	950
20	10...40	1000
20	10...38	1050


Electrical data controls input

Specification item	Value	Unit	Condition
Control method	DALI-2, PUSH SWITCH, CLO		
Dimming range	1...100%	%	


Wiring and connections

Specification item	Value	Unit	Condition
Input wire cross section	0.75...2.5 / 18...13	mm ² / AWG	E - N - L, double connectors for looping
Input wire strip length	10...11	mm	
Output wires cross section	0.5...1.5 / 20...15	mm ² / AWG	LED
Output wire strip length	8...9	mm	
Control wire cross section	0.5...1.5 / 20...15	mm ² / AWG	DA/N - DA/Ls double connectors for looping
Control wire strip length	8...9	mm	
Max. cable length		cm	For additional details for regulations see pages info 12-14

Wiring diagrams




PUSH SWITCH diagram - Collegamento PUSH SWITCH



DALI diagram - Collegamento DALI

Dimensions




Insulation

Specification item	Output	Controls	Earth
Input	double or reinforced	basic	double or reinforced
Output	N/A	double or reinforced	N/A
Control			double or reinforced

Operation temperatures and humidity

Specification item	Value	Unit	Condition
Ambient temperature	-25...50	°C	
Tc	85	°C	Maximum temperature measured at Tc point
Maximum housing temperature	110	°C	In case of failure

Temperature/Life



Storage temperature and humidity

Specification item	Value	Unit	Condition
Ambient temperature	-30...85	°C	
Relative humidity	5...85	%	Non condensing

Programmable features

Specification item	Available	Default setting	Condition
Set Adjustable Output Current (AOC)	DIP-SWITCH	300mA	
Push Switch	Yes	ON	
Min Dimming Level	Yes	1%	
CLO	Yes	OFF	
DALI part 251	Yes	OFF	

Features

Specification item	Value	Condition
Open load	Yes	
Short circuit	Yes	
Over load and thermal protection	Yes	C.5.a
Hot plug	No	
Suitable for fixtures with protection class	class I/II	
DALI part 101	Yes	
DALI part 102	Yes	
DALI part 207	Yes	
DALI part 252	Yes	
DALI part 253	Yes	

In rush current

Specification item	Value	Unit	Condition
In rush current	5/50	A / usec	
Drivers / MCB 16A type B	50	pcs	

Driver touch current / protective conductor current

Specification item	Value	Unit	Condition
Typical Protective Conductor Current	0,2	mA	

Surge immunity

Specification item	Value	Unit	Condition
Mains surge immunity (diff. mode)	2	kV	
Mains surge immunity (comm. mode)	4	kV	

Application info

Specification item	Value
Approval marks	CE ENEC EAC RCM (DO NOT COVER order code 127481ASN) UKCA
Ingress Protection classification (IP)	20
Application	Compact dimmable indoor
Mounting type	Indipendent
Cut hole diameter	Ø88

Performance curves

