


## Fog\_s 125 | 10 W | diffuse | Wall recessed

Also available for wall/ceiling and ceiling recessed

### Technical Specifications

Source lamp	LED 10 W
Total wattage	12
Voltage	220-240 Vac - 50/60 Hz
Control	On/Off (other controls on request)
Luminous flux (*Source flux)	490 lm (1300 lm*) @ 3000 K
Luminous efficacy	41 lm/W @ 3000 K
Light Temperature	2700 K
McADAM steps	3
Beam	diffuse
CRI	>90
Life time	L80-B15 > 60.000 h Ta 40°C
IP rating	67
IK rating	10
Insulation class	I
Note	Control on request: DALI - 1/10V - DMX - TRIAC Light control on request: 2200K - 4000K - RGBW



### Materials

Body	Die-cast aluminium EN47100
Diffuser	Opal glass
Finishing	White - Polyester powder paint

## Included accessories

---

-	0.5 m length cable -05RN-F
-	Housing box

---

## Available accessories

---

0404M025	Four way connection box
----------	-------------------------


---

0303004	Glass lifting suction pad
---------	---------------------------

---

00KCG0.03	Recessed box adjusting kit
-----------	----------------------------

---



---

0404M011	Single connection IP68
----------	------------------------

