



4.0

LED PCB 8W | 350mA | 22V
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80/50K

wire springs 118x36 L60 4-28

2700K/3000K | CRI >90 | 4x125lm

	CODE
	109161WW9
	109161BB9

ALWAYS USE

driver | 350mA

	CODE
10W dim	90223406
14W DALI	90243502

more options and specs on page 896

4.1

LED PCB 8W | 350mA | 22V
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80/50K

wire springs 63x59 L60 4-28

2700K/3000K | CRI >90 | 4x125lm

	CODE
	109261WW9
	109261BB9

ALWAYS USE

driver | 350mA

	CODE
10W dim	90223406
14W DALI	90243502

more options and specs on page 896

8.0

LED PCB 16W | 700mA | 22V
aluminium | polycarbonate
light colour selectable via dip switch

IP20 M-39° L80/50K

wire springs 226x36 L60 4-28

2700K/3000K | CRI >90 | 8x125lm

	CODE
	109361WW9
	109361BB9

ALWAYS USE

driver | 700mA

	CODE
20W dim	90225604
14W DALI	90245704

more options and specs on page 900

