

PROJECTOR



Wattage	5 W
Voltage	24 Vdc
Beam	
Adjustability	180° 360°
Technology	

Wattage	5 W
Voltage	24 Vdc
Beam	
Adjustability	180° 360°
Technology	


TECHNICAL SPECIFICATIONS

	SPOT
Source lamp	LED 5 W
Total wattage	5 W
Voltage	24 Vdc
Control	Power supply not included (other controls on request*)
Light colour	2700 K • 3000 K • 4000 K (other colours on request**)
Luminous flux	360 lm (480 lm***)
Luminous efficacy	72 lm/W
McADAM steps	3
Beam	12°
CRI	> 90
Life time	L80-B15 > 60.000 h T _a 40°C
IP rating	IP 67
IK rating	IK 08
Insulation class	III

- * **Control available on request**
DALI - 1/10V - DMX - TRIAC

** **Light colour available on request**
2200 K • RGBW

*** Source flux



FLOOD

LED 5 W

5 W

24 Vdc

Power supply not included
(other controls on request*)2700 K • 3000 K • 4000 K
(other colours on request**)

310 lm (480 lm***)

62 lm/W

3

40°


> 90

L80-B15 > 60.000 h Ta 40°C

IP 67

IK 08

III

**E (LUX)**

H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	594	594	0.7
2.00	149	149	1.4
3.00	66	66	2.1
4.00	37	37	2.8
5.00	24	24	3.5

DIFFUSE

LED 5 W

5 W

24 Vdc

Power supply not included
(other controls on request*)2700 K • 3000 K • 4000 K
(other colours on request**)

88 lm (480 lm***)

17.6 lm/W

3

90°


> 90

L80-B15 > 60.000 h Ta 40°C

IP 67

IK 08

III

**E (LUX)**

H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	48	48	1.9
2.00	12	12	3.9
3.00	5	5	5.8
4.00	3	3	7.8
5.00	2	2	9.7

MATERIALS

Body

Extruded aluminium EN AW6060

Diffuser

Extra clear tempered glass 8 mm
Frosted tempered glass 8 mm (for diffuse beam)

Finishing

Polyester powder paint

ORDER CODE

LY 3 0 PRO _ _ B 7 Z _

Finishing

H

Grey

L

Graphite

Light colour

N

4000 K

H

3000 K

Y

2700 K

Beam

S

Spot

F

Flood

D

Diffuse

Example

LY 3 0 PRO **S** N B 7 Z **L****INCLUDED ACCESSORIES**

Code

Description

Page

-

1 m length cable -05RN-F

-

AVAILABLE ACCESSORIES

Code

Description

Page

00A469

Mounting spike

567

00KVISLY30_Visor (available in different colours,
see accessories section)

573

0404M009

Single connection IP68

574

0409BT014Transformer _ 24 Vdc - 12 W
(connect up to 1 pc)

574

0409BT015Transformer _ 24 Vdc - 25 W
(connect up to 3 pcs)

574

0409BT016Transformer _ 24 Vdc - 100 W
(connect up to 12 pcs)

575