

FLOOR RECESSED




Wattage	5 W
Voltage	24 Vdc
Beam	
Technology	

Wattage	5 W
Voltage	24 Vdc
Beam	
Technology	


TECHNICAL SPECIFICATIONS

Source lamp	SPOT
Total wattage	LED 5 W
Voltage	5 W
	24 Vdc
Control	Power supply not included (other controls on request*)
Light colour	2700 K • 3000 K • 4000 K (other colours on request**)
Luminous flux	360 lm (480 lm***)
Luminous efficacy	72 lm/W
McADAM steps	3
Beam	12°
CRI	> 90
Life time	L80-B15 > 60.000 h Ta 40°C
IP rating	IP 67
IK rating	IK 08
Insulation class	III

- * Control available on request
DALI - 1/10V - DMX - TRIAC
- ** Light colour available on request
2200 K • RGBW
- *** Source flux



E (LUX)			
H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	4402	4402	0.2
2.00	1101	1101	0.4
3.00	489	489	0.6
4.00	275	275	0.8
5.00	176	176	1



FLOOD

LED 5 W

5 W

24 Vdc

Power supply not included
(other controls on request*)2700 K • 3000 K • 4000 K
(other colours on request**)

310 lm (480 lm***)

62 lm/W

3

40°


> 90

L80-B15 > 60.000 h Ta 40°C

IP 67

IK 08

III

**E (LUX)**

H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	594	594	0.7
2.00	149	149	1.4
3.00	66	66	2.1
4.00	37	37	2.8
5.00	24	24	3.5

DIFFUSE

LED 5 W

5 W

24 Vdc

Power supply not included
(other controls on request*)2700 K • 3000 K • 4000 K
(other colours on request**)

88 lm (480 lm***)

17.6 lm/W

3

90°


> 90

L80-B15 > 60.000 h Ta 40°C

IP 67

IK 08

III

**E (LUX)**

H (m)	lux (3000 K)	lux (4000 K)	Ø (m)
1.00	48	48	1.9
2.00	12	12	3.9
3.00	5	5	5.8
4.00	3	3	7.8
5.00	2	2	9.7

MATERIALS

Body

Extruded aluminium EN AW6060

Diffuser

Extra clear or frosted tempered glass 8 mm

Finishing

Polyester powder paint

ORDER CODE

MI 3 0 IPT _ _ B 7 Z _

Finishing

H Grey

L Graphite

Light colour

N 4000 K

H 3000 K

Y 2700 K

Beam

S Spot

F Flood

D Diffuse

Example

MI 3 0 IPT S N B 7 Z H

INCLUDED ACCESSORIES

Code	Description	Page
-	1 m length cable -05RN-F	-
-	Housing box	-

AVAILABLE ACCESSORIES

Code	Description	Page
0404M009	Single connection IP68	574
0409BT014	Transformer _ 24 Vdc - 12 W (connect up to 1 pc)	574
0409BT015	Transformer _ 24 Vdc - 25 W (connect up to 3 pcs)	574
0409BT016	Transformer _ 24 Vdc - 100 W (connect up to 12 pcs)	575