

STEP LIGHT

SPECIFICATIONS

MOUNTING		WALL RECESSED
POWER	[W]	3
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	240
LIGHT COLOUR	[K]	3000
CRI		>90
BEAM ANGLE	[°]	60°
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	80

POWER SUPPLY	[V] [A]	220-240V AC 50/60 Hz
LED-DRIVER		INCLUDED
DIMMING		NO
THROUGH-WIRING		NO

MATERIAL		ALUMINUM
INGRESS PROTECTION		IP65
PROTECTION CLASS		I
IMPACT PROTECTION		n/A
NET WEIGHT	[kg]	0,24
GROSS WEIGHT	[kg]	0,28

COLOUR (HOUSING)		WHITE ~RAL9003
COLOUR (HOUSING)		BLACK ~RAL9004
CUT-OUT (fixture)	[mm]	66x70
CUT-OUT (mounting box)	[mm]	80x80




LIGHT DISTRIBUTION

n/a

*Luminous flux values are nominal LED

OPTIONS / OPTIONAL ACCESSORIES

Colours




white


black

MOUNTING DIMENSIONS



FIXTURE



MOUNTINGBOX



FIXTURE DIMENSIONS



DLS LIGHTING

www.dlsighting.com

***DLS**
LIGHTING