

VEGAS 45

SPECIFICATIONS

MOUNTING		CEILING RECESSED
POWER	[W]	6
LAMP		build-in LED
LUMINOUS FLUX*	[lm]	420
COLOUR TEMPERATURE	[K]	2700
CRI		>90
BEAM ANGLE		30°
AVERAGE LIFETIME	[h]	L80/B50,000
LUMINOUS EFFICACY	[lm/W]	70
POWER SUPPLY	[V] [A]	150mA CC
LED-DRIVER		NOT INCLUDED
DIMMING		SEE DRIVER
THROUGH-WIRING		SEE DRIVER
MATERIAL		ALUMINUM
INGRESS PROTECTION		IP20
PROTECTION CLASS		III
NET WEIGHT	[kg]	0.09
GROSS WEIGHT	[kg]	0.11
COLOUR (HOUSING)		WHITE ~RAL9003
COLOUR (HOUSING)		BLACK ~RAL9005
CUT-OUT	[mm]	Ø45
RECESSED DEPTH (H)	[mm]	70

*Luminous flux values are nominal LED data at a operating temperature of 25° C

OPTIONS / OPTIONAL ACCESSORIES

REFLECTOR	22° / 43°
-----------	-----------



LIGHT DISTRIBUTION

30°


Colours:




black/black



black/white





white/white




white/black

CUT OUT DIMENSIONS mm



FIXTURE DIMENSIONS mm



DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING