






# BLIEK petit

Ceiling recessed



## 1.0

LED COB 6W | 350mA | 17V  
aluminium

IP20 0°-60°/355° A 31° SDCM2 L70|55K 0.20kg

wire springs 086-89 1.60 4-23

## 2.0

2x LED COB 6W | 700mA | 17V  
aluminium




IP20 0°-60°/355° A 31° SDCM2 L70|55K 0.40kg

wire springs 087x176 1.60 4-23

## 1.0 TRIMLESS

LED COB 6W | 350mA | 17V  
aluminium

IP20 0°-60°/355° A 31° SDCM2 L70|55K 0.17kg



### OPTIONAL

honeycomb louver

CODE 90051131

CODE	
164461W_	164461CH_
164461B_	

LIGHT COLOUR	LUMEN   CRI	CODE
2700K	470   >90	3
3000K	500   >90	5
2000-3000K   16V	355   >90	9

### ALWAYS USE

driver | 350mA

CODE	
6W	90213303
10W dim	90223406
14W DALI	90243501

more options and specs on page 806

Rev. 001/2024-03

### CODE

164561W_
164561CH_
164561B_

LIGHT COLOUR	LUMEN   CRI	CODE
2700K	470   >90	3
3000K	500   >90	5
2000-3000K   16V	355   >90	9

### ALWAYS USE

alu plasterkit 078-80 1.80 12,5, 15, 20, 25  
CODE

90017210

driver | 350mA

CODE	
6W	90213303
10W dim	90223406
14W DALI	90243501

more options and specs on page 806

### ALWAYS USE

driver | 700mA | only 1x needed

CODE	
15W dim	90225502
28W DALI	90245704

more options and specs on page 809