



MATCH point

Ceiling recessed



reddot winner 2023



As awarded by The Chicago Athenaeum: Museum of Architecture and Design



ø45



ø45



ø26

1.0

LED COB 5W | 250mA | 18V
aluminium

IP20 32° SDCM2 L80|50K 0.06kg

wire springs 40-41 68 4-25

CODE

191161W_
191161B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	320	>90	3
3000K	350	>90	5

ALWAYS USE

driver | 250mA

CODE

5W dim	90226201
13W DALI*	90246501

*revision opening required
more options and specs on page 806

1.0 IP44

LED COB 5W | 250mA | 18V
aluminium

IP44 32° SDCM2 L80|50K 0.06kg

wire springs 40-41 68 4-25

CODE

191261W_
191261B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	300	>90	3
3000K	330	>90	5

ALWAYS USE

driver | 250mA

CODE

5W dim IP20	90226201
13W DALI IP20*	90246501

*revision opening required
more options and specs on page 806

1.0 TRIMLESS

LED COB 5W | 250mA | 18V
aluminium

IP20 32° SDCM2 L80|50K 0.08kg

45-47 60 4-26

CODE

191861B_

LIGHT COLOUR	LUMEN	CRI	CODE
2700K	270	>90	3
3000K	300	>90	5

ALWAYS USE

driver | 250mA

CODE

5W dim	90226201
13W DALI	90246501

revision opening required
more options and specs on page 806