

FLOOR RECESSED



Wattage	5 W
Voltage	220-240 Vac
Beam	
Technology	

Wattage	5 W
Voltage	220-240 Vac
Beam	
Technology	


TECHNICAL SPECIFICATIONS

Source lamp	SPOT
Total wattage	LED 5 W
Voltage	5 W
Control	220-240 Vac, 50-60Hz
Light colour	On/Off (other controls on request*)
Luminous flux	2700 K • 3000 K (other colours on request**)
Luminous efficacy	330 lm (400 lm***)
McADAM steps	66 lm/W
Beam	3
CRI	12°
Life time	> 80
IP rating	L80-B15 > 60.000 h Ta 40°C
IK rating	IP 67
Insulation class	IK 08
	II


- * Control available on request
DALI - 1/10V - DMX - TRIAC

** Light colour available on request
2200 K • 4000 K • RGBW

*** Source flux



E (LUX)		
H (m)	lux (3000 K)	Ø (m)
1.00	4819	0.2
2.00	1205	0.4
3.00	535	0.6
4.00	300	0.8
5.00	190	1



MEDIUM

LED 5 W

5 W

220-240 Vac, 50-60Hz

On/Off (other controls on request*)

2700 K • 3000 K
(other colours on request**)

294 lm (400 lm***)

59 lm/W

3

30°

> 80

L80-B15 > 60.000 h Ta 40°C

IP 67

IK 08

II

DIFFUSE

LED 5 W

5 W

220-240 Vac, 50-60Hz

On/Off (other controls on request*)

2700 K • 3000 K
(other colours on request**)

93 lm (400 lm***)

18.6 lm/W

3

90°



> 80

L80-B15 > 60.000 h Ta 40°C

IP 67

IK 08

II

**E (LUX)**

H(m)	lux (3000 K)	Ø(m)
1.00	524	0.6
2.00	131	1.2
3.00	58	1.8
4.00	33	2.4
5.00	21	3

E (LUX)

H(m)	lux (3000 K)	Ø(m)
1.00	56	1.8
2.00	14	3.5
3.00	6	5.3
4.00	3	7.1
5.00	2	8.9

MATERIALS

Body

Extruded aluminium EN AW6060

Diffuser

Extra clear or frosted tempered glass 8 mm

Finishing

Polyester powder paint

ORDER CODE

MI 33 IPT _ _ A 10 _

Finishing

H Grey

L Graphite

Light colour

H 3000 K

Y 2700 K

Beam

S Spot

M Medium

D Diffuse

Example

MI 33 IPT MHA10 L

INCLUDED ACCESSORIES

Code	Description	Page
-	1 m length cable -05RN-F	-
-	Housing box	-

AVAILABLE ACCESSORIES

Code	Description	Page
0404M009	Single connection IP68	574