



RAY

Wall surface

189

317 | 343 | 355

469

ø150

ø150

ø150

1.0 LED

LED PCB 6W | phase-cut dim  
220-240VAC | 50-60Hz  
aluminium

IP20 SDCM3 L80|55K 0.62kg

|  | CODE     |
|--|----------|
|  | 342168W_ |
|  | 342168L_ |
|  | 342168G_ |
|  | 342168M_ |
|  | 342168Q_ |
|  | 342168P_ |
|  | 342168B_ |

incl. adjustable flaps

| LIGHT COLOUR | LUMEN CRI | CODE |
|--------------|-----------|------|
| 2700K        | 350 >90   | 3    |
| 3000K        | 370 >90   | 5    |
| 1800-2850K   | 330 >90   | 9    |

2.0 LED

LED PCB 11W | phase-cut dim  
220-240VAC | 50-60Hz  
aluminium

IP20 SDCM3 L80|55K 0.69kg

|  | CODE     |
|--|----------|
|  | 342148W_ |
|  | 342148L_ |
|  | 342148G_ |
|  | 342148M_ |
|  | 342148Q_ |
|  | 342148P_ |
|  | 342148B_ |

incl. adjustable flaps

| LIGHT COLOUR | LUMEN CRI | CODE |
|--------------|-----------|------|
| 2700K        | 2x440 >90 | 3    |
| 3000K        | 2x460 >90 | 5    |
| 1800-2850K   | 2x410 >90 | 9    |

1.0 QT14

QT14 max. 75W | G9  
220-240VAC | 50-60Hz  
aluminium

IP20 0.62kg

|  | CODE     |
|--|----------|
|  | 3221G0W0 |
|  | 3221G0L0 |
|  | 3221G0G0 |
|  | 3221G0M0 |
|  | 3221G0Q0 |
|  | 3221G0P0 |
|  | 3221G0B0 |

OPTIONAL

flaps for adjustable beam angle

|  | CODE     |
|--|----------|
|  | 900401W0 |

QT14 3W | G9 | phase-cut dim | clear

|               | CODE     |
|---------------|----------|
| 2700K   300lm | 9010G802 |
| 3000K   280lm | 9010G804 |

Rev. 001/2024-11

WEVER & DUCRÉ 544 — 545