


SIDECAR S OnOff

“Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden”.


LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral premium driver.
Low ripple output current <4% to assure camera and scanner friendly performance.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	760g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 34pcs/MCB 16A type B
Ripple out. current	< 4%. Flicker-free performance
Colour consistency	2 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Not dimmable



- White
- Black



Accessories

Honeycomb louvre Sidecar S **213091**

SIDECAR S OnOff

Description	Reflector	CCT (K)	CRI	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																													
LIGHTSOURCE					LUMINAIRE			ART. No.																																																																														
WARM WHITE 3000K (930)																																																																																						
SIDECAR S OnOff 2000lm SP 930	Spot 15°	3000K	92	2320	16W	2180	136	213110	213114																																																																													
SIDECAR S OnOff 2000lm ME 930	Medium 25°	3000K	92	2320	16W	2180	136	213111	213115																																																																													
SIDECAR S OnOff 2000lm FL 930	Flood 40°	3000K	92	2320	16W	2180	136	213112	213116																																																																													
SIDECAR S OnOff 2000lm WFL 930	Widefl. 60°	3000K	92	2320	16W	2180	136	213113	213117																																																																													
SIDECAR S OnOff 3000lm SP 930	Spot 15°	3000K	92	3380	25W	3175	126	213210	213214																																																																													
SIDECAR S OnOff 3000lm ME 930	Medium 25°	3000K	92	3380	25W	3175	126	213211	213215																																																																													
SIDECAR S OnOff 3000lm FL 930	Flood 40°	3000K	92	3380	25W	3175	126	213212	213216																																																																													
SIDECAR S OnOff 3000lm WFL 930	Widefl. 60°	3000K	92	3380	25W	3175	126	213213	213217																																																																													
Spot2000lm3000lm <table><tr><td>m</td><td>Ø</td><td>Lux</td><td>Lux</td></tr><tr><td>1</td><td>0,28</td><td>14169</td><td>20548</td></tr><tr><td>2</td><td>0,56</td><td>3542</td><td>5137</td></tr><tr><td>3</td><td>0,84</td><td>2267</td><td>2283</td></tr><tr><td>4</td><td>1,12</td><td>885</td><td>1284</td></tr></table> Medium2000lm3000lm <table><tr><td>m</td><td>Ø</td><td>Lux</td><td>Lux</td></tr><tr><td>1</td><td>0,42</td><td>7887</td><td>11446</td></tr><tr><td>2</td><td>0,84</td><td>1972</td><td>2861</td></tr><tr><td>3</td><td>1,25</td><td>876</td><td>1272</td></tr><tr><td>4</td><td>1,70</td><td>493</td><td>715</td></tr></table> Flood2000lm3000lm <table><tr><td>m</td><td>Ø</td><td>Lux</td><td>Lux</td></tr><tr><td>1</td><td>0,74</td><td>4514</td><td>6550</td></tr><tr><td>2</td><td>1,42</td><td>1128</td><td>1637</td></tr><tr><td>3</td><td>2,18</td><td>502</td><td>728</td></tr><tr><td>4</td><td>2,91</td><td>282</td><td>409</td></tr></table> Wideflood2000lm3000lm <table><tr><td>m</td><td>Ø</td><td>Lux</td><td>Lux</td></tr><tr><td>1</td><td>1,19</td><td>2401</td><td>3488</td></tr><tr><td>2</td><td>2,38</td><td>600</td><td>872</td></tr><tr><td>2,5</td><td>2,97</td><td>384</td><td>558</td></tr><tr><td>3</td><td>3,56</td><td>267</td><td>218</td></tr></table>					m	Ø	Lux	Lux	1	0,28	14169	20548	2	0,56	3542	5137	3	0,84	2267	2283	4	1,12	885	1284	m	Ø	Lux	Lux	1	0,42	7887	11446	2	0,84	1972	2861	3	1,25	876	1272	4	1,70	493	715	m	Ø	Lux	Lux	1	0,74	4514	6550	2	1,42	1128	1637	3	2,18	502	728	4	2,91	282	409	m	Ø	Lux	Lux	1	1,19	2401	3488	2	2,38	600	872	2,5	2,97	384	558	3	3,56	267	218	3000K 930 Spectral power distributions	
m	Ø	Lux	Lux																																																																																			
1	0,28	14169	20548																																																																																			
2	0,56	3542	5137																																																																																			
3	0,84	2267	2283																																																																																			
4	1,12	885	1284																																																																																			
m	Ø	Lux	Lux																																																																																			
1	0,42	7887	11446																																																																																			
2	0,84	1972	2861																																																																																			
3	1,25	876	1272																																																																																			
4	1,70	493	715																																																																																			
m	Ø	Lux	Lux																																																																																			
1	0,74	4514	6550																																																																																			
2	1,42	1128	1637																																																																																			
3	2,18	502	728																																																																																			
4	2,91	282	409																																																																																			
m	Ø	Lux	Lux																																																																																			
1	1,19	2401	3488																																																																																			
2	2,38	600	872																																																																																			
2,5	2,97	384	558																																																																																			
3	3,56	267	218																																																																																			
NEUTRAL WHITE 4000K (940)																																																																																						
SIDECAR S OnOff 2000lm SP 940	Spot 15°	4000K	92	2330	16W	2185	137	213150	213154																																																																													
SIDECAR S OnOff 2000lm ME 940	Medium 25°	4000K	92	2330	16W	2185	137	213151	213155																																																																													
SIDECAR S OnOff 2000lm FL 940	Flood 40°	4000K	92	2330	16W	2185	137	213152	213156																																																																													
SIDECAR S OnOff 2000lm WFL 940	Widefl. 60°	4000K	92	2330	16W	2185	137	213153	213157																																																																													
SIDECAR S OnOff 3000lm SP 940	Spot 15°	4000K	92	3460	25W	3255	130	213250	213254																																																																													
SIDECAR S OnOff 3000lm ME 940	Medium 25°	4000K	92	3460	25W	3255	130	213251	213255																																																																													
SIDECAR S OnOff 3000lm FL 940	Flood 40°	4000K	92	3460	25W	3255	130	213252	213256																																																																													
SIDECAR S OnOff 3000lm WFL 940	Widefl. 60°	4000K	92	3460	25W	3255	130	213253	213257																																																																													
Spot2000lm3000lm <table><tr><td>m</td><td>Ø</td><td>Lux</td><td>Lux</td></tr><tr><td>1</td><td>0,28</td><td>14545</td><td>21085</td></tr><tr><td>2</td><td>0,56</td><td>3636</td><td>5271</td></tr><tr><td>3</td><td>0,84</td><td>1616</td><td>2343</td></tr><tr><td>4</td><td>1,12</td><td>972</td><td>1318</td></tr></table> Medium2000lm3000lm <table><tr><td>m</td><td>Ø</td><td>Lux</td><td>Lux</td></tr><tr><td>1</td><td>0,42</td><td>8097</td><td>11738</td></tr><tr><td>2</td><td>0,84</td><td>2024</td><td>2934</td></tr><tr><td>3</td><td>1,25</td><td>900</td><td>1304</td></tr><tr><td>4</td><td>1,70</td><td>506</td><td>734</td></tr></table> Flood2000lm3000lm <table><tr><td>m</td><td>Ø</td><td>Lux</td><td>Lux</td></tr><tr><td>1</td><td>0,74</td><td>4631</td><td>6717</td></tr><tr><td>2</td><td>1,42</td><td>1158</td><td>1679</td></tr><tr><td>3</td><td>2,18</td><td>515</td><td>746</td></tr><tr><td>4</td><td>2,91</td><td>289</td><td>420</td></tr></table> Wideflood2000lm3000lm <table><tr><td>m</td><td>Ø</td><td>Lux</td><td>Lux</td></tr><tr><td>1</td><td>1,19</td><td>2468</td><td>3577</td></tr><tr><td>2</td><td>2,38</td><td>617</td><td>894</td></tr><tr><td>2,5</td><td>2,97</td><td>395</td><td>572</td></tr><tr><td>3</td><td>3,56</td><td>274</td><td>397</td></tr></table>					m	Ø	Lux	Lux	1	0,28	14545	21085	2	0,56	3636	5271	3	0,84	1616	2343	4	1,12	972	1318	m	Ø	Lux	Lux	1	0,42	8097	11738	2	0,84	2024	2934	3	1,25	900	1304	4	1,70	506	734	m	Ø	Lux	Lux	1	0,74	4631	6717	2	1,42	1158	1679	3	2,18	515	746	4	2,91	289	420	m	Ø	Lux	Lux	1	1,19	2468	3577	2	2,38	617	894	2,5	2,97	395	572	3	3,56	274	397	4000K 940 Spectral power distributions	
m	Ø	Lux	Lux																																																																																			
1	0,28	14545	21085																																																																																			
2	0,56	3636	5271																																																																																			
3	0,84	1616	2343																																																																																			
4	1,12	972	1318																																																																																			
m	Ø	Lux	Lux																																																																																			
1	0,42	8097	11738																																																																																			
2	0,84	2024	2934																																																																																			
3	1,25	900	1304																																																																																			
4	1,70	506	734																																																																																			
m	Ø	Lux	Lux																																																																																			
1	0,74	4631	6717																																																																																			
2	1,42	1158	1679																																																																																			
3	2,18	515	746																																																																																			
4	2,91	289	420																																																																																			
m	Ø	Lux	Lux																																																																																			
1	1,19	2468	3577																																																																																			
2	2,38	617	894																																																																																			
2,5	2,97	395	572																																																																																			
3	3,56	274	397																																																																																			

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.