



**1.0 LED**

LED LED COB 12W | dimmable  
220-240VAC | 50-60Hz | incl. driver  
aluminium

IP20 0°-25°|355° 34° SDCM2 L80|55K 0.65kg

phase-cut dim

	CODE
	133764W_
	133764J_
	133764H_
	133764K_
	133764CH_
	133764P_
	133764Q_
	133764B_

DALI-2 | push dim

	CODE
	133765W_
	133765J_
	133765H_
	133765K_
	133765CH_
	133765P_
	133765Q_
	133765B_

LIGHT COLOUR	LUMEN CRI	CODE
2700K	745 >90	3
3000K	800 >90	5
2000-3000K	560 >90	9




MORE BEAM ANGLES ONLINE

[weverducre.com/more-solid](http://weverducre.com/more-solid)

Rev. 001/2024-05

**SOLID**

Ceiling surface



**1.0 PAR16**

PAR16 max. 12W | GU10  
100-240VAC | 50-60Hz  
aluminium

IP20 0°-25°|355° 0.61kg

	CODE
	133120W0
	133120J0
	133120H0
	133120K0
	133120CH0
	133120P0
	133120Q0
	133120B0

**OPTIONAL**

PAR16 6.5W | GU10 | phase-cut dim

	CODE
	901228W3
	901228B3
	901228W5
	901228B5