

558

wall-i 160

WALL LAMP



Wattage	5.5 W single emission 8 W double emission
Voltage	20-240 Vac
Beam	


TECHNICAL SPECIFICATIONS

Source lamp	SPOT
Total wattage	LED 5.5 W
Voltage	8.5 W
Control	220-240 Vac, 50-60Hz
Light colour	On/Off (other controls on request*)
Luminous flux	2700 K • 3000 K (other colours on request**)
Luminous efficacy	609 lm (715 lm***)
McADAM steps	76 lm/W
Beam	3
CRI	20°
Life time	> 90
IP rating	L80-B15 > 60.000 h Ta 40°C
IK rating	IP 66
Insulation class	IK 08
	II


- * Control available on request
DALI - 1/10V - DMX - TRIAC

** Light colour available on request
2200 K • 4000 K • RGBW

*** Source flux



E (LUX)		
H (m)	lux (3000 K)	Ø (m)
1.00	2889	0.37
2.00	722	0.75
3.00	321	1.12
4.00	181	1.49
5.00	116	1.86



MEDIUM

LED 5.5 W

8.5 W

220-240 Vac, 50-60Hz

On/Off (other controls on request*)

2700 K • 3000 K
(other colours on request**)

589 lm (715 lm***)

74 lm/W

3

30°

> 90

L80-B15 > 60.000 h Ta 40°C

IP 66

IK 08

II

WIDE FLOOD

LED 5.5 W

8.5 W

220-240 Vac, 50-60Hz

On/Off (other controls on request*)

2700 K • 3000 K
(other colours on request**)

491 lm (715 lm***)

61 lm/W

3

55°

> 90

L80-B15 > 60.000 h Ta 40°C

IP 66

IK 08

II

ELLIPTIC

LED 5.5 W

8.5 W

220-240 Vac, 50-60Hz

On/Off (other controls on request*)

2700 K • 3000 K
(other colours on request**)

592 lm (715 lm***)

74 lm/W

3

20° x 50°

> 90

L80-B15 > 60.000 h Ta 40°C

IP 66

IK 08

II

ASYMMETRIC

LED 5.5 W

8.5 W

220-240 Vac, 50-60Hz

On/Off (other controls on request*)

2700 K • 3000 K
(other colours on request**)

266 lm (715 lm***)

33 lm/W

3

70° x 840°


> 90

L80-B15 > 60.000 h Ta 40°C


IP 66

IK 08

II

**E (LUX)**

H (m)	lux (3000 K)	Ø (m)
1.00	1952	0.51
2.00	488	1
3.00	217	1.52
4.00	122	2.02
5.00	78	2.53

**E (LUX)**

H (m)	lux (3000 K)	Ø (m)
1.00	545	1.05
2.00	136	2.11
3.00	61	3.16
4.00	34	4.22
5.00	22	5.27

