



Zefiro H 600 NEW




Designed by FLOS Outdoor, 2013



LED source included. Integrated electric power supply 220-240V ON/OFF and adjustable light intensity from 1 to 10V or DALI. Equipped with a protruding, neoprene, one meter cable and a 2-way IP68 H2O connection system. It can be installed on any ground using studs or a recessed fixing plate with mortar, to be ordered separately. Mid-Night version available upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793663203	
Mounting	Ground	
Environments	onments Outdoor wet location	
Light source type	LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	1	
Power (W)	12	
System power (W)	14.5	
Source flux (lm)	1716	
Lumen Output (lm)	1357	

Physical

Colour	Anthracite
Orientation	Fixed
Net weight (kg)	3.88
Package height (mm)	190
Package width (mm)	615
Package length (mm)	175
Package volume (m3)	0.02
IP internal	65

Download

Mounting instructions

₹ ZIP

Photometric Files

LDT / IES

₹ ZIP

Technical Drawings

2D	业 ZIP
3D	↓ ZIP

https://professional.flos.com/en/global/product/zefiro-h-600-fa53201733.a/

FA53201733.A

Schematic light drawing



Beam	Angle:	126°
h(m)	E(lx)	D(m)
1	113	3.57
2	28	7.15
3	13	10.72
4	7	14.29
5	5	17.86

Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	126
Beam angle C90-270 (°)	126
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	No
Dimming interface	Not Dimmable
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply





F990F00A000

S.P.D. (SURGE PROTECTION DEVICE)



OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles IP68 H2O stop. (ø5,5÷12mm cable)



OPTIONAL Accessory

FA21

Base Plate and Fixing Bolts Zefiro



OPTIONAL Accessory

FA185.A

high resistance in-ground box for installation